


<b>DRAWING NUMBER:</b>	<b>01-1010-1-XXXX</b>
<b>PRODUCT GROUP:</b>	BINDING POSTS
<b>SUB-GROUP:</b>	MILITARY BINDING POSTS
<b>DESCRIPTION:</b>	WATERTIGHT BINDING POST



- 1-DISC ,TOP-BRASS
- 2-HOUSING-BRASS
- 3-CONTACT-BRASS
- 4-STEM(3/4)-BRASS
- 5-SPRING-ST.ST.
- 6-STEM(1")-BRASS
- 7-GASKET-RUBBER
- 8-INSULATOR-NYLON
- 9-GASKET-RUBBER
- 10-INSULATOR-NYLON
- 11-WASHER-BRASS
- 12-LOCKWASHER-BRASS
- 13-NUT-STEEL
- 14-CAP-RUBBER
- 15-CAP-RUBBER
- 16-STEM(13/32)-BRASS
- 17-STEM(5/5)-BRASS
- 18-POLYBAG
- 19-STEM(3/4)-BRASS
- 20-CAP-RUBBER
- 21-CAP-RUBBER

OVERALL LENGTH	BOARD / PANEL MOUNTING METHOD	MOUNTING HOLE SIZE	DRILL SIZE	BOARD / PANEL THICKNESS
2.000" REF.	THREAD MOUNT (10-32 NUT)	0.312" ± 0.002"	5/16"	1/16" - 1/8"

**PART NO. STRUCTURE:**

01-1010 - 1 - XX XX  
 PART SERIES    DIMENSION    FINISH    INSULATION COLOR

**MATERIAL OPTIONS:**

**01-1010-1-XXXX**

COMPONENT	MATERIAL	MATERIAL AND SPECIFICATION
BODY	BRASS	BRASS PER ASTM B16, ALLOY C36000
HEAD	BRASS	BRASS PER ASTM B16, ALLOY C36000
INSULATION*	NYLON	NYLON
SPRING (CAGE)	STAINLESS STEEL	STAINLESS STEEL
NUT	STEEL	STEEL
WASHER	BRASS	BRASS

\*For Insulation color, please see INSULATION COLOR OPTIONS on Page 2

FINISH - PLATING OPTIONS:

01-1010-1-XXXX

FINISH CODE	COMPONENT	FINISH	FINISH AND SPECIFICATION
02	BODY	NICKEL WITH HOT TIN DIP END	NICKEL PER SAE-AMS-QQ-N-290, WITH HOT TIN DIPPED END OF SOLDER TERMINAL
	HEAD	NICKEL	NICKEL PER SAE-AMS-QQ-N-290
	SPRING (CAGE)	NICKEL	NICKEL
	NUT	NICKEL	NICKEL
	WASHER	NICKEL	NICKEL

INSULATION COLOR OPTIONS:

01-1010-1-XXXX

INSULATION COLOR	BLACK	RED
COLOR CODE NO.	10	12

TOLERANCES:\*

DECIMAL	FRACTIONAL	ANGULAR	DRAWING ORIENTATION DATE	LAST MODIFICATION DATE
± 0.005	± 1/64	± 1/2 °	10/9/1995	5/1/2017

\*All dimensions are in inches.

RoHS COMPLIANCE:

01-1010-1-02XX

PART NUMBER	RoHS COMPLIANT
01-1010-1-0210	NO
01-1010-1-0212	NO

MILITARY REFERENCE SPECIFICATIONS:

01-1010-1-02XX

PART NUMBER	MIL SPECIFICATION	MIL PART NUMBER	COMMERCIAL ITEM DESCRIPTION (CID) SPECIFICATION	CID PART NUMBER
01-1010-1-0210	MIL-P-55149/8	PB08NA01	A-A-59559	AA59559-1 (N/A~.)
01-1010-1-0212	MIL-P-55149/8	PB08NA02	A-A-59559	AA59559-2 (N/A~.)

NOTES:

**DATASHEET NOTES**

DESIGNED FOR APPLICATIONS WHERE PANEL MOUNTING MUST BE WATERTIGHT. CAP MOUNTS IN 5/16" HOLE IN PANELS FROM 1/16" TO 1/8" THICK. DEPRESSING SPRING LOADED CAP OPENS SLOT FOR WIRE. SUPPLIED WITH HARDWARE.

**INSTRUCTION NOTES**

SUPPLIED WITH: ONE NICKEL PLATED STEEL #10 HEX NUT, ONE NICKEL PLATED BRASS SPLIT #10 LOCKWASHER, ONE NICKEL PLATED BRASS #10 FLAT WASHER, TWO NYLON WASHERS, TWO RUBBER GASKETS. P/N 01-1010-1-0210 SUPPLIED WITH BLACK RUBBER CAP. P/N 01-1010-1-0212 SUPPLIED WITH RED RUBBER CAP.