


<b>DRAWING NUMBER:</b>	<b>15R-349-X-XX</b>
<b>PRODUCT GROUP:</b>	TERMINALS
<b>SUB-GROUP:</b>	MILITARY NON-INSULATED TERMINALS
<b>DESCRIPTION:</b>	NON-INSULATED THRU-HOLE DOUBLE TURRET TERMINAL



BOARD / PANEL MOUNTING METHOD	MOUNTING HOLE SIZE	DRILL SIZE	FEED THRU COMBINATION
SWAGE MOUNT	0.116" ± 0.001	#32	N/A

**PART NO. STRUCTURE:**

15R-349 - X - XX  
PART SERIES    DIMENSION    FINISH

**MATERIAL OPTIONS:**

15R-349-X-XX

COMPONENT	MATERIAL	MATERIAL AND SPECIFICATION
TERMINAL	PHOSPHOR BRONZE	PHOSPHOR BRONZE PER ASTM B139, ALLOY C54400

**DIMENSION OPTIONS:**

15R-349-X-XX

DIMENSION	K	OVERALL LENGTH	SHANK LENGTH (L)	BOARD/PANEL THICKNESS
2	N/A	0.437"	0.109"	1/16"
3	N/A	0.469"	0.141"	3/32"
4	N/A	0.500"	0.172"	1/8"

FINISH - PLATING OPTIONS:

15R-349-X-XX

FINISH CODE	COMPONENT	FINISH	FINISH AND SPECIFICATION
05	TERMINAL	ELECTRO-SOLDER	0.000300"MIN. ELECTRO-SOLDER PER SAE-AMS-P-81728 OVER 0.000100"MIN. COPPER PER SAE-AMS-2418
088	TERMINAL	BRIGHT TIN-LEAD	0.000300"MIN. BRIGHT TIN-LEAD (Sn93%-Pb7%) PER ASTM B545 OVER 0.000100"MIN. COPPER PER SAE-AMS-2418
095	TERMINAL	HOT SOLDER DIP	0.000100"MIN. HOT SOLDER DIP USING Sn60 PER IPC-J-STD-006 OVER 0.000100"MIN. COPPER PER SAE-AMS-2418

TOLERANCES:\*

DECIMAL	FRACTIONAL	ANGULAR	DRAWING ORIGATION DATE	LAST MODIFICATION DATE
± 0.005	N/A	N/A	8/22/1997	3/1/2017

\*All dimensions are in inches.

RoHS COMPLIANCE:

15R-349-2-XX

15R-349-3-XX

15R-349-4-XX

PART NUMBER	RoHS COMPLIANT
15R-349-2-05	NO
15R-349-2-088	NO
15R-349-2-095	NO

PART NUMBER	RoHS COMPLIANT
15R-349-3-05	NO
15R-349-3-088	NO
15R-349-3-095	NO

PART NUMBER	RoHS COMPLIANT
15R-349-4-05	NO
15R-349-4-088	NO
15R-349-4-095	NO

MILITARY REFERENCE SPECIFICATIONS:

15R-349-2-XX

PART NUMBER	MIL SPECIFICATION	MIL PART NUMBER	COMMERCIAL ITEM DESCRIPTION (CID) SPECIFICATION	CID PART NUMBER
15R-349-2-05	MIL-T-55155/17	M55155/17XB01 (M55155/17-1Z; SE17XC01Z)	A-A-59126/17	AA59126/17XB01
15R-349-2-088	MIL-T-55155/17	M55155/17XD01	A-A-59126/17	AA59126/17XD01
15R-349-2-095	MIL-T-55155/17	M55155/17XC01	A-A-59126/17	AA59126/17XC01

15R-349-3-XX

PART NUMBER	MIL SPECIFICATION	MIL PART NUMBER	COMMERCIAL ITEM DESCRIPTION (CID) SPECIFICATION	CID PART NUMBER
15R-349-3-05	MIL-T-55155/17	M55155/17XB02 (M55155/17-2Z; SE17XC02Z)	A-A-59126/17	AA59126/17XB02
15R-349-3-088	MIL-T-55155/17	M55155/17XD02	A-A-59126/17	AA59126/17XD02
15R-349-3-095	MIL-T-55155/17	M55155/17XC02	A-A-59126/17	AA59126/17XC02

Continued on next page...

MILITARY REFERENCE SPECIFICATIONS CONTINUED:

15R-349-4-XX

PART NUMBER	MIL SPECIFICATION	MIL PART NUMBER	COMMERCIAL ITEM DESCRIPTION (CID) SPECIFICATION	CID PART NUMBER
15R-349-4-05	MIL-T-55155/17	M55155/17XB03 (M55155/17-3Z; SE17XC03Z)	A-A-59126/17	AA59126/17XB03
15R-349-4-088	MIL-T-55155/17	M55155/17XD03	A-A-59126/17	AA59126/17XD03
15R-349-4-095	MIL-T-55155/17	M55155/17XC03	A-A-59126/17	AA59126/17XC03

TOOLING:

INSTALLATION TOOL: ARBOR PRESS	INSTALLATION TOOL: ANVIL (ARBOR PRESS OPERATED)	INSTALLATION TOOL: PRESS-FIT / ROLL SWAGE / RIVET PUNCH (ARBOR PRESS OPERATED)	INSTALLATION TOOL: FLARE SWAGE PUNCH (ARBOR PRESS OPERATED)
TM1	TA188-146-31	TP112-78	TFLP90-200

NOTES:

DATASHEET NOTES
N/A

INSTRUCTION NOTES
SEE GENERAL SWAGING INSTALLATION INSTRUCTION ON CONCORD ELECTRONICS' WEBSITE <a href="http://WWW.CONCORD-ELECTRONICS.COM">WWW.CONCORD-ELECTRONICS.COM</a>